

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 433 447 B1

(12)

EUROPEAN PATENT SPECIFICATION(45) Date of publication of patent specification: **22.06.94** (51) Int. Cl.⁵: **A61M 29/00**(21) Application number: **88906888.8**(22) Date of filing: **12.08.88**(86) International application number:
PCT/JP88/00803(87) International publication number:
WO 89/01351 (23.02.89 89/05)(54) **CATHETER.**(30) Priority: **13.08.87 JP 202397/87**(43) Date of publication of application:
26.06.91 Bulletin 91/26(45) Publication of the grant of the patent:
22.06.94 Bulletin 94/25(84) Designated Contracting States:
BE DE FR GB IT NL SE(56) References cited:
EP-A- 0 033 659
JP-A- 6 282 975
US-A- 4 503 569

PATENT ABSTRACTS OF JAPAN, vol. 1, no.
17, 23rd January 1986; & JP-A-60 169 551
(HITACHI KINZOKU K.K.) 03-09-1985

(73) Proprietor: **TERUMO KABUSHIKI KAISHA**
No. 44-1, Hatagaya 2-chome,
Shibuya-ku
Tokyo 151(JP)(72) Inventor: **HARADA, Fumiaki**
Terumo Kabushiki Kaisha 2656-1
Ohbuchi Fuji-shi Shizuoka-ken 417(JP)(74) Representative: **Casalonga, Axel et al**
BUREAU D.A. CASALONGA - JOSSE
Morassistrasse 8
D-80469 München (DE)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

EP 0 433 447 B1

Description

Technical Field

The present invention relates to a catheter for inserting or removing an expansion holder for holding an inner diameter of an internal cavity of a tubular organ.

Background Art

An expansion holder (to be also called a stent hereinafter) is generally used to hold an internal diameter of an internal cavity of a tubular organ so as to prevent a stenosed portion of, e.g., a coronary artery from being stenosed again after the stenosed portion is expanded by a blood vessel expansion catheter.

A conventional stent used for the above purpose is a net made of a stainless steel wire (Surgery, 1986, Vol. 99, No. 2, p. 199 - 205) or a stent made of a unidirectional shape memory alloy (Published Examined Japanese Patent Application No. 61-6655). When a blood vessel is to be held expanded by using this stainless steel stent, the stent is inserted to a predetermined position of the blood vessel through a blood vessel expansion catheter, and a balloon arranged at the distal end of the catheter is expanded to expand the stent to the same diameter of the blood vessel. When a stent made of a unidirectional shape memory alloy is used, it is inserted to a predetermined position of a blood vessel and is warmed with warm water, thereby expanding the stent.

In either case, the stent is simply wound around and held at the distal end portion of the catheter. The outer diameter of a catheter portion around which the stent is wound is larger than that of other catheter portions. As a result, when a catheter is inserted in a relatively thin blood vessel such as a coronary artery, or when the catheter mounted with this stent is inserted into a guide catheter, the sliding operation of the catheter is degraded due to the presence of the stent mounting portion, thus posing a problem. In addition, since a conventional stent inserting/removing catheter does not have any means for assuring a position of the distal end of the catheter or a positional relationship between the catheter distal end and the indwelled stent, it is difficult to operate such a conventional catheter.

A catheter of the above described type is also known from US-A-4 503 569, which forms the closest prior art.

It is an object of the present invention to provide a stent inserting/removing catheter which can be smoothly slid within a blood vessel and in a guide catheter, can assure a position of a distal

end portion, and can improve operability.

Disclosure of Invention

In order to solve the above problem, the present invention reduces the outer diameter of a stent mounting portion at a distal end portion of a catheter to prevent this mounting portion from having an outer diameter larger than that of other catheter portions even if a stent is mounted thereon, and employs a means for forming an X-ray non-transmission marker on a small-diameter portion of the stent mounting portion, as needed.

More specifically, according to the present invention, there is provided a catheter characterized by comprising a catheter tube having an open proximal end or two open ends and at least one side opening formed on a circumferential wall near a distal end of the catheter tube to communicate with an opening at the proximal end, a hub portion formed to communicate with the opening at the proximal end of the catheter tube, and an expansion holder for holding an inner diameter of an internal cavity of a tubular organ, the expansion holder being made of a shape memory alloy cylinder which can radially expand or contract upon changes in temperature, and the expansion holder being mounted to cover at least part of a catheter tube portion corresponding to the side opening, wherein an outer diameter of the catheter tube portion corresponding to the side opening is smaller than that of other catheter tube portions, and the expansion holder is mounted on the catheter tube portion corresponding to the side opening so that an outer diameter of the expansion holder is equal to or smaller than that of the other catheter tube portions.

Furthermore, according to the present invention, there is provided a catheter having an X-ray non-transmitting marker on at least part of the catheter tube portion corresponding to the side opening.

Moreover, according to the present invention, there is provided the expansion holder comprising a helical member made of a unidirectional or bidirectional shape memory alloy.

The hub portion of the catheter may comprise a branched hub having at least one branch port. A check valve may be arranged in one of the ports.

The shape memory alloy according to the present invention has a transformation temperature and is deformed into a memory shape when it is heated to the transformation temperature or more. The unidirectional shape memory alloy can be freely deformed at the transformation temperature or less, and keeps the memory shape upon being heated to the transformation temperature or more even when the alloy is cooled to the transformation

temperature or less unless an external force is not applied thereto. The bidirectional shape memory alloy additionally has a memory shape at the transformation temperature or less and is reversibly deformed into one of the two shapes with respect to the transformation temperature as a boundary.

In the catheter according to the present invention, since the stent can be mounted on a catheter tube portion near its distal end such that the outer diameter of the stent mounting portion is not larger than that of other catheter tube portions, sliding resistance can be greatly reduced when the catheter tube is inserted into the guide catheter or a blood vessel, thereby improving operability. In addition, since the marker made of an X-ray non-transmission material is formed on the stent mounting portion, the position of the distal end of the catheter or the relationship between the indwelled stent and the distal end of the catheter can be clearly assured. Other additional effects can also be obtained. For example, when branch ports are formed in the hub portion, a cooling liquid or various liquid medicines solutions can be injected without requiring removal of a circuit device for measuring a pressure and the like.

Brief Description of Drawings

Fig. 1 is a side view of a catheter according to the present invention, Fig. 2 is a side view showing a state wherein a stent is removed from the catheter, Fig. 3 is a side view showing a structure of the stent, Fig. 4 is an enlarged sectional view of a hub portion of the catheter, Fig. 5 is a side view showing a state wherein the catheter according to the present invention is inserted into a blood vessel, and Fig. 6 corresponds to Fig. 5 and is a side view showing a state wherein the stent is expanded and indwelled in the blood vessel.

Best Mode of Carrying Out the Invention

The present invention will be described with reference to the illustrated embodiment.

Fig. 1 shows an embodiment of a catheter according to the present invention. The catheter comprises a catheter tube 11 having two open ends, a hub portion 12 arranged to communicate with an opening at the proximal end of the catheter tube 11, and a spiral expansion holder (stent) 13 mounted on the distal end portion of the catheter tube 11. A portion of the catheter tube 11 which receives the stent 13 thereon constitutes a small-diameter portion 11a having an outer diameter smaller than that of other catheter tube portions. Therefore, when the stent 13 is mounted on the small-diameter portion 11a, the outer diameter of the stent 13 is equal to or smaller than that of other

catheter tube portions. In other words, the outer diameter of the small-diameter portion 11a of the catheter tube 11 is smaller than the outer diameter of other catheter tube portions by an amount corresponding to twice or more the wall thickness of the stent 13.

A large number of side openings 14 which communicate with the opening at the proximal end of the catheter tube 11 to supply a stent cooling liquid are formed in the circumferential wall surface of the small-diameter portion 11a. Fig. 2 shows a state wherein the spiral stent 13 (Fig. 3) is removed from the assembly shown in Fig. 1, thus clearly illustrating the state of the side openings 14. The shape of each side opening 14 is not limited to the illustrated circular shape, but may be a slit-like shape. In addition, the number of side openings 14 is not limited to a specific number, but can be arbitrarily selected.

A distal end portion 11b of the catheter tube 11 has an outer diameter equal to that of the proximal portion and has a spherical end face. A hole is formed at the center of the distal end portion 11b to receive a guide wire therethrough. Ring markers 15 made of an X-ray non-transmission material such as gold are formed at both ends of the small-diameter portion 11a.

The hub portion 12 has a pair of branch ports 16a and 16b, so that a cooling liquid and various liquid medicines can be injected without removing a pressure measuring circuit device and the like. Alternatively, only one branch port may be provided, and a three-port cock or the like may be mounted in this branch port. As shown in Fig. 4, the proximal end of the hub portion 12 is open and a check valve 17 made of a flexible material such as silicone rubber is arranged near the opening of the proximal end. Therefore, the guide wire or the like can be inserted through the proximal end of the hub portion 12 while maintaining liquid tightness.

Generally, a thermoplastic resin (e.g., an ethylene-vinyl acetate copolymer) is preferably used as a material of the catheter tube 11. Similarly, a thermoplastic resin (e.g., polycarbonate) is generally used to form the hub portion 12. As shown in Fig. 4, the hub portion 12 is connected to the proximal end portion of the catheter tube 11.

(Example 1)

A bidirectional shape memory alloy (a Ni-Ti binary alloy consisting essentially of 51 atm% of Ni and the balance substantially F) manufactured into a stent 13 by a predetermined method was formed into a spiral shape, as shown in Fig. 3, and the spiral stent 13 was inserted around the small-diameter portion 11a of the catheter tube 11 in an

expanded shape while being maintained at 35°C or more. The expanded stent 13 was cooled to a temperature of 20°C or less by using a physiological saline cooled with ice and contracted and was brought into tight contact with the small-diameter portion 11a. The outer diameter of the stent 13 was thus set to be equal to or slightly smaller than that of other portions of the catheter tube 11. The physiological saline cooled with ice was flowed out from the side openings 14 through the port 16b. As shown in Fig. 5, the stent 13 was inserted to the target indwelling portion through the guide catheter 18 by utilizing the guide wire 19 while the stent 13 was kept contracted. In this case, the guide catheter 18 was inserted in a blood vessel 20 in advance. This operation was performed under X-ray transmission scopy fluoroscopy. The position of the stent 13 was easily confirmed by the markers 15 mounted on the small-diameter portion 11a of the catheter tube 11. When the stent 13 reached this indwelling portion, and supply of the physiological saline cooled with ice was stopped, the stent 13 was gradually warmed by the body temperature. When the small-diameter portion was warmed to the body temperature (35°C), the stent 13 was expanded, and was brought into contact with the inner wall surfaces of the blood vessel 20, and was held at this position, as shown in Fig. 6. The distal end of the catheter tube 11 could be easily removed from the stent 13 while the stent 13 was indwelled at a predetermined position of the blood vessel 20. When a predetermined period of time elapsed after the indwelling operation, the catheter tube 11 was inserted into the blood vessel 20 again, and a contrast medium was injected into the blood vessel 20 through the port 16a to check whether thrombi or the like were attached to the stent 13. If so, an appropriate infusion solution such as urokinase was injected from the port 16a to dissolve the thrombi. The physiological saline cooled with ice was injected from the port 16b to cool and contract the stent 13. The stent 13 was brought into contact with the small-diameter portion 11a of the catheter tube 11 and could be removed from the indwelling portion.

(Example 2)

A unidirectional shape memory alloy (a Ni-Ti binary alloy consisting essentially of 50 atm% of Ni and the balance substantially Fe) manufactured into a stent 13 by a predetermined method was formed into a spiral shape, as shown in Fig. 3. A shape was memorized such that this stent 13 could be deformed to be brought into contact with the small-diameter portion 11a of the catheter tube 11 at 40°C or less but was expanded at 50°C or more to be brought into contact with a predetermined

indwelling portion.

As shown in Fig. 1, the stent 13 was brought into tight contact with the small-diameter portion 11a of the catheter tube 11 to set the outer diameter of the stent 13 to be equal to or smaller than that of other portions of the catheter tube 11, as shown in Fig. 1. As shown in Fig. 5, the stent 13 was inserted to the target indwelling portion through the guide catheter 18. A contrast medium was injected from the port 16b, and a stenosed portion at the indwelling portion was checked by transmission scopy and at the same time pressures at the proximal and distal portions of this portion were measured via the port 16a to appropriately determine the degree of stenosis. An appropriate liquid medicines such as urokinase was injected from the port 16b, and an appropriate treatment was performed for the indwelling portion. A warm physiological saline at 50°C or more was supplied from the port 16b to the side openings 14 to change the shape of the stent 13 in an expanded shape and to indwell the stent 13 at this portion. Thereafter, a contrast medium was injected from the port 16b to check indwelling of the stent under fluoroscopy, and at the same time pressures at the proximal and distal end portions of the indwelling portion were measured via the port 16a to confirm there was no pressure gradient. The catheter 11 was then removed from the body.

Industrial Applicability

The catheter according to the present invention is useful in medical operations which aim at temporarily or permanently expanding and holding the inner diameter of an internal cavity of a blood vessel or any other tubular organ.

Claims

1. A catheter comprising a catheter tube (11) having an open proximal end and at least one side opening formed on a circumferential wall near a distal end of said catheter tube to communicate with an opening at said proximal end, a hub portion (12) formed to communicate with said opening at said proximal end of said catheter tube, an expansion holder (13) for holding an inner diameter of an internal cavity of a tubular organ, said expansion holder being made of a shape memory alloy cylinder which can radially expand or contract upon changes in temperature, and said expansion holder being mounted to cover at least part of a catheter tube portion (11a) corresponding to said side opening, an outer diameter of said catheter tube portion (11a) corresponding to said side opening being smaller than that of other cath-

ter tube portions, and said expansion holder (13) is mounted on said catheter tube portion (11a) corresponding to said side opening characterized in that an outer diameter of said expansion holder is equal to or smaller than that of other catheter tube portions and said catheter tube may have two open ends.

2. A catheter according to claim 1, wherein at least one X-ray non-transmission marker is formed on said catheter tube portion corresponding to said side opening.
3. A catheter according to claims 1 or 2, wherein at least one port is added to said hub.
4. A catheter according to any preceding claim, characterized in that at least part of a distal end portion in front of said catheter tube portion corresponding to the side opening has an outer diameter substantially equal to that of said other catheter tube portions.
5. A catheter according to any preceding claim, wherein said expansion holder has a helical shape.
6. A catheter according to any preceding claim wherein said shape memory alloy exhibits unidirectional shape memory properties.
7. A catheter according to any one of claims 1 to 5 wherein said shape memory alloy exhibits bidirectional shape memory properties.

Patentansprüche

1. Katheter, umfassend einen Katheterschlauch (11) mit einem offenen proximalen Ende und mindestens einer in einer Umfangswand nahe einem distalen Ende des Katheterschlauches geformten Seitenöffnung für Verbindung mit einer Öffnung am proximalen Ende, einen (Anschluß-)Stutzenabschnitt (12), der für Verbindung mit der Öffnung am proximalen Ende des Katheterschlauches geformt ist, (und) einen Expansionshalter (13) zum Aufrechterhalten eines Innendurchmessers eines inneren Hohlraums eines rohr- oder schlauchförmigen Organs, wobei der Expansionshalter aus einem Zylinder aus einer Formgedächtnislegierung geformt ist, der sich bei Temperaturänderungen radial aufzuweiten oder zusammenzuziehen vermag, wobei der Expansionshalter so angebracht ist, daß er zumindest einen Teil eines Katheterschlauchabschnitts (11a) entsprechend der Seitenöffnung verdeckt, wobei ein Außendurchmesser des Katheterschlauch-

abschnitts (11a) entsprechend der Seitenöffnung kleiner ist als derjenige von anderen Katheterschlauchabschnitten und wobei der Expansionshalter (13) an dem der Seitenöffnung entsprechenden Katheterschlauchabschnitt (11a) angebracht ist, dadurch gekennzeichnet, daß ein Außendurchmesser des Expansionshalters gleich groß oder kleiner ist als derjenige von anderen Katheterschlauchabschnitten und daß der Katheterschlauch zwei offene Enden aufweisen kann.

2. Katheter nach Anspruch 1, wobei mindestens ein für Röntgenstrahlung nicht durchlässiger Markierer an dem der Seitenöffnung entsprechenden Katheterschlauchabschnitt geformt ist.
3. Katheter nach Anspruch 1 oder 2, wobei am Stutzen(abschnitt) mindestens ein Zulaß hinzugefügt ist.
4. Katheter nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß mindestens ein Teil eines distalen Endabschnitts vor der Seitenöffnung entsprechenden Katheterschlauchabschnitts einen Außendurchmesser aufweist, der im wesentlichen demjenigen der anderen Katheterschlauchabschnitte gleich ist.
5. Katheter nach einem der vorangehenden Ansprüche, wobei der Expansionshalter eine wellenartige Form besitzt.
6. Katheter nach einem der vorangehenden Ansprüche, wobei die Formgedächtnislegierung unidirektionale bzw. einseitig gerichtete Formgedächtniseigenschaften aufweist.
7. Katheter nach einem der Ansprüche 1 bis 5, wobei die Formgedächtnislegierung bidirektionale bzw. zweiseitig gerichtete Formgedächtniseigenschaften aufweist.

Revendications

1. Cathéter comprenant un tube de cathéter (11) avec une extrémité proximale ouverte et au moins un orifice latéral formé sur une paroi de la circonférence, près d'une extrémité distale dudit tube de cathéter, pour communiquer avec un orifice se trouvant en ladite extrémité proximale, une partie manchon (12) formée pour communiquer avec ledit orifice au niveau de ladite extrémité proximale dudit tube de cathéter, un dispositif de retenue par expansion (13) pour maintenir le diamètre intérieur de la cavité intérieure d'un organe tubulaire,

- ledit dispositif de retenue par expansion étant fait d'un cylindre en alliage à mémoire de forme qui peut se dilater ou se contracter radialement lors de variations de température , et ledit dispositif de retenue par expansion étant monté pour recouvrir une partie au moins d'un tronçon (11a) du tube de cathéter qui correspond audit orifice latéral, le diamètre extérieur dudit tronçon (11a) de tube de cathéter qui correspond audit orifice latéral étant plus petit que celui des autres tronçons du tube de cathéter, et le dispositif de retenue par expansion (13) est monté sur ledit tronçon (11a) du tube de cathéter qui correspond audit orifice latéral, caractérisé en ce que le diamètre extérieur dudit dispositif de retenue par expansion est égal ou inférieur à celui des autres tronçons du tube de cathéter et ledit tube de cathéter peut avoir deux extrémités ouvertes.
- 20
2. Cathéter selon la revendication 1, dans lequel au moins une marque ne transmettant pas les rayons X est formée sur ledit tronçon de tube de cathéter qui correspond audit orifice latéral.
- 25
3. Cathéter selon les revendications 1 ou 2, dans lequel au moins une embouchure est ajoutée audit manchon.
- 30
4. Cathéter selon l'une quelconque des précédentes revendications, caractérisé en ce qu'une partie au moins du tronçon d'extrémité distale en avant du tronçon de tube de cathéter qui correspond audit orifice latéral a un diamètre extérieur sensiblement égal à celui des autres tronçons du tube de cathéter.
- 35
5. Cathéter selon l'une quelconque des précédentes revendications, dans lequel ledit dispositif de retenue par expansion a une forme hélicoïdale.
- 40
6. Cathéter selon l'une quelconque des précédentes revendications, dans lequel ledit alliage à mémoire de forme présente des propriétés unidirectionnelles de mémoire de forme.
- 45
7. Cathéter selon l'une quelconque des revendications 1 à 5, dans lequel ledit alliage à mémoire de forme présente des propriétés bidirectionnelles de mémoire de forme.
- 50




FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6